

6 5 4 3 2 1

MATERIAL AND FINISH

Insulator: Polycarbonate, UL-94V-0 rated
 Contacts: Brass, Nickel plated

Distributed by Electro-Stock, Inc. sales@electrostock.com
 630-682-1542 Fax 630-682-1562 http://www.electrostock.com


ELECTRICAL SPECIFICATIONS:




Current rating: 10 A
 Voltage rating: 250 VAC

ORDERING CODE:

42R04- $\frac{1}{1}$ $\frac{1}{2}$

1) ELECTRICAL CIRCUIT CONFIGURATION

1 = 10A 250V 70°C
 2+GROUND     

2 = 10A 250V 120°C
 2+GROUND   

2) COLOR
 1 = BLACK
 2 = GRAY

NOTE:
 Contains integral cable clamp strain relief & internal screw type connections. Maximum wire gauge is 16AWG stranded.

TOLERANCE UNLESS OTHERWISE SPECIFIED		
X	±	1
X.X	±	0.4
X.XX	±	0.20
DRAWN BY	GQ	DATE: 08/17/01
CHECK BY	TD	DATE: 08/20/01
APPR BY	PB	DATE: 08/21/01

Power Dynamics, Inc.
 Phone: 973 560-0019 Whippany, New Jersey Fax: 973 560-0076

PART: IEC 60320 C14 MALE POWER CORD PLUG
 R/A LEFT HANDED CONNECTION

42R04-X1X1

SIZE: A
 SCALE: NTS

ALL DIMENSIONS FOR REFERENCE ONLY
 DIMENSIONS ARE IN MILLIMETERS

SHEET 1 of 1
 REV:

D

C

B

A

REVISIONS
 CHANGE
 CHNG
 CHECK
 APPR
 REV
 DATE

6 5 4 3 2 1